



# HCF65TF180F


650V N-Channel Super Junction Power MOSFET

## ●Features:

- 20.0A, 650V,  $R_{DS(on)(Typ)} = 180m\Omega @ V_{GS}=10V$
- Ultra Low Gate Charge
- Ultra Low  $C_{rss}$
- 100% Avalanche Tested
- Fast Switching
- Improved dv/dt Capability

## ●Application:

- High Frequency Switching Mode Power Supply
- Active Power Factor Correction



### Absolute Maximum Ratings ( $T_c=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Value	Unit
$V_{DSS}$	Drain-Source Voltage	650	V
$V_{GSS}$	Gate-Source Voltage	$\pm 30$	V
$I_D$	Drain Current	- Continuous ( $T_c=25^\circ C$ )	20.0*
		- Continuous ( $T_c=100^\circ C$ )	12.5*
$I_{DM}$	Drain Current - Pulsed (Note1)	60*	A
$P_D$	Power Dissipation ( $T_c = 25^\circ C$ ) - Derate above $25^\circ C$	34	W
		0.27	W/ $^\circ C$
$E_{AS}$	Single Pulsed Avalanche Energy (Note2)	600	mJ
$I_{AR}$	Avalanche Current (Note1)	7	A
$E_{AR}$	Repetitive Avalanche Energy, $t_{AR}$ limited by $T_{jmax}$ (Note1)	1	mJ
dv/dt	Drain Source voltage slope, $V_{DS} \leq 480V$	50	V/ns
dv/dt	Reverse diode dv/dt, $V_{DS} \leq 480V, I_{SD} \leq I_D$	15	V/ns
$T_j$	Operating Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature Range	-55 to +150	$^\circ C$

\* Drain Current Limited by Maximum Junction Temperature.

### Thermal Characteristics

Symbol	Parameter	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case	3.67	$^\circ C / W$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	62.5	$^\circ C / W$



# HCF65TF180F

650V N-Channel Super Junction Power MOSFET


## Electrical Characteristics (Tc=25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
<b>Off Characteristics</b>						
BV <sub>DSS</sub>	Drain-source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	650	--	--	V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =650V, V <sub>GS</sub> =0V	--	--	1	μA
		V <sub>DS</sub> =650V, Tc=125°C	--	--	100	μA
I <sub>GSSF</sub>	Gate-Body Leakage Current, Forward	V <sub>GS</sub> =+30V, V <sub>DS</sub> =0V	--	--	100	nA
I <sub>GSSR</sub>	Gate-Body Leakage Current, Reverse	V <sub>GS</sub> =-30V, V <sub>DS</sub> =0V	--	--	-100	nA
<b>On Characteristics</b>						
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	2.0	--	4.0	V
R <sub>DS(on)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =10 V, I <sub>D</sub> =10.0A	--	180	210	mΩ
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =10 V, I <sub>D</sub> =10.0A	--	15	--	S
<b>Dynamic Characteristics</b>						
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =50V, V <sub>GS</sub> =0V, f=1.0MHz	--	1440	--	pF
C <sub>oss</sub>	Output Capacitance		--	105	--	pF
C <sub>rss</sub>	Reverse Transfer Capacitance		--	3.94	--	pF
Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> = 480V, I <sub>D</sub> =20 A, V <sub>GS</sub> = 10 V	--	23.3	--	nC
Q <sub>gs</sub>	Gate-Source Charge		--	6.6	--	nC
Q <sub>gd</sub>	Gate-Drain Charge		--	8.3	--	nC
R <sub>G</sub>	Intrinsic gate resistance	f=1MHz open drain		1		Ω
<b>Switching Characteristics</b>						
t <sub>d(on)</sub>	Turn-On Delay Time	V <sub>DD</sub> = 480V, I <sub>D</sub> =20 A, R <sub>G</sub> =25 Ω, V <sub>GS</sub> =10 V	--	40.3	--	ns
t <sub>r</sub>	Turn-On Rise Time		--	49.3	--	ns
t <sub>d(off)</sub>	Turn-Off Delay Time		--	60	--	ns
t <sub>f</sub>	Turn-Off Fall Time		--	59.2	--	ns
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>						
I <sub>SD</sub>	Maximum Continuous Drain-Source Diode Forward Current		--	--	20	A
I <sub>SDM</sub>	Maximum Pulsed Drain-Source Diode Forward Current		--	--	60	A
V <sub>SD</sub>	Drain-Source Diode Forward Voltage	T <sub>J</sub> = 25°C , V <sub>GS</sub> =0V, I <sub>SD</sub> =20.0A	--	--	1.2	V
t <sub>rr</sub>	Reverse Recovery Time	T <sub>J</sub> = 25°C , I <sub>F</sub> =20.0A, dI <sub>F</sub> /dt=100A/μs	--	367	--	ns
Q <sub>rr</sub>	Reverse Recovery Charge		--	4.2	--	μC
I <sub>rrm</sub>	Peak Reverse Recovery Current		--	24.3	--	A


**Notes:**

- 1、Repetitive Rating:Pulse Width Limited by Maximum Junction Temperature.
- 2、T<sub>J</sub> = 25°C , V<sub>DD</sub> = 50V, V<sub>G</sub> =10V, R<sub>G</sub> = 25 Ω.


### On-Regin Characteristics




### On-Resistance Variation vs. Drain Current and Gate Voltage




### Capacitance Characteristics




### Transfer Characteristics



### Body Diode Forward Voltage Variation vs. Source Current and Temperature



### Gate Charge Characteristics







# HCF65TF180F

## 650V N-Channel Super Junction Power MOSFET


**Breakdown Voltage Variation vs. Temperature**




**On-Resistance Variation vs. Temperature**



**Maximum Safe Operating Area**



**Maximum Drain Current Vs. Case Temperature**



### TO-220F Package Dimensions

UNIT: mm

SYMBOL	min	nom	max	SYMBOL	min	nom	max
A	9.80		10.60	D		2.54	
A1		7.00		D1	1.15		1.55
A2	2.90		3.40	D2	0.60		1.00
A3	9.10		9.90	D3	0.20		0.50
B1	15.40		16.40	E	2.24		2.84
B2	4.35		4.95	E1		0.70	
B3	6.00		7.40	E2		1.0×45°	
C	3.00		3.70	E3	0.35		0.65
C1	15.00		17.00	E4	2.30		3.30
C2	8.80		10.80	α (度)		30°	

