



## SMT20N65


650V N-Channel MOSFET

### ● Features:

- 20.0A, 650V,  $R_{DS(on)(Typ)}$  = 380mΩ@ $V_{GS}$ =10V
- Low Gate Charge
- Low  $C_{rss}$
- 100% Avalanche Tested
- Fast Switching
- Improved dv/dt Capability

### ● Application:

- High Frequency Switching Mode Power Supply
- Active Power Factor Correction



### Absolute Maximum Ratings( $T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
$V_{DSS}$	Drain-Source Voltage	650	V
$I_D$	Drain Current - Continuous( $T_c=25^\circ\text{C}$ )	20.0*	A
	- Continuous( $T_c=100^\circ\text{C}$ )	12.6*	A
$I_{DM}$	Drain Current -Pulsed (Note1)	80.0*	A
$V_{GSS}$	Gate-Source Voltage	$\pm 30$	V
$E_{AS}$	Single Pulsed Avalanche Energy ( Limit Reference Value ) (Note2)	1078	mJ
$I_{AR}$	Avalanche Current (Note1)	14.0	A
$E_{AR}$	Repetitive Avalanche Energy (Note1)	33	mJ
$dv/dt$	Peak Diode Recovery $dv/dt$ (Note3)	4.5	V/ns
$P_D$	Power Dissipation( $T_c = 25^\circ\text{C}$ ) -Derate above $25^\circ\text{C}$	265	W
		2.12	W/ $^\circ\text{C}$
$T_j$	Operating Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-55 to +150	$^\circ\text{C}$

\* Drain Current Limited by Maximum Junction Temperature.

### Thermal Characteristics

Symbol	Parameter	Max	Unit
$R_{\theta JC}$	Thermal Resistance,Junction to Case	0.47	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance,Junction to Ambient	62.5	$^\circ\text{C}/\text{W}$

	SMT20N65						
	650V N-Channel MOSFET						

### Electrical Characteristics(Tc=25°C unless otherwise noted)

Symbol	Parameter	Test Conditons	Min	Typ	Max	Unit
<b>Off Characteristics</b>						
BV <sub>DSS</sub>	Drain-source Breakdown Voltage	V <sub>GS</sub> =0V ,I <sub>D</sub> =250μA	650	--	--	V
△BV <sub>DSS</sub> /△T <sub>J</sub>	Breakdown Voltage Temperature Coefficient	I <sub>D</sub> =250μA (Referenced to 25°C)	--	0.68	--	V/°C
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =650V,V <sub>GS</sub> =0V	--	--	1	μA
		V <sub>DS</sub> =520V,Tc=125°C	--	--	10	μA
I <sub>GSSF</sub>	Gate-Body Leakage Current,Forward	V <sub>GS</sub> =+30V, V <sub>DS</sub> =0V	--	--	100	nA
I <sub>GSSR</sub>	Gate-Body Leakage Current,Reverse	V <sub>GS</sub> =-30V, V <sub>DS</sub> =0V	--	--	-100	nA
<b>On Characteristics</b>						
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> =250μA	2.0	--	4.0	V
R <sub>DS(on)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =10 V, I <sub>D</sub> =10.0A	--	380	450	mΩ
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =20 V, I <sub>D</sub> =10.0A (Note4)	--	18	--	S
<b>Dynamic Characteristics</b>						
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =25V,V <sub>GS</sub> =0V, f=1.0MHz	--	3050	--	pF
C <sub>oss</sub>	Output Capacitance		--	240	--	pF
C <sub>rss</sub>	Reverse Transfer Capacitance		--	9	--	pF
<b>Switching Characteristics</b>						
t <sub>d(on)</sub>	Turn-On Delay Time	V <sub>DD</sub> = 325 V, I <sub>D</sub> = 20 A, R <sub>G</sub> = 25 Ω (Note4,5)	--	27.2	--	ns
t <sub>r</sub>	Turn-On Rise Time		--	44.5	--	ns
t <sub>d(off)</sub>	Turn-Off Delay Time		--	82.5	--	ns
t <sub>f</sub>	Turn-Off Fall Time		--	44.4	--	ns
Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> = 520 V, I <sub>D</sub> =20 A, V <sub>GS</sub> = 10 V (Note4,5)	--	55.2	--	nC
Q <sub>gs</sub>	Gate-Source Charge		--	13.9	--	nC
Q <sub>gd</sub>	Gate-Drain Charge		--	22.8	--	nC
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>						
I <sub>s</sub>	Maximum Continuous Drain-Source Diode Forward Current	--	--	20	--	A
I <sub>SM</sub>	Maximum Pulsed Drain-Source Diode Forward Current	--	--	80	--	A
V <sub>SD</sub>	Drain-Source Diode Forward Voltage	V <sub>GS</sub> =0V,I <sub>s</sub> =20 A	--	--	1.4	V
t <sub>rr</sub>	Reverse Recovery Time	V <sub>GS</sub> =0V, I <sub>s</sub> =20 A, d I <sub>F</sub> /dt=100A/μs (Note4)	--	593	--	ns
Q <sub>rr</sub>	Reverse Recovery Charge		--	7.62	--	μC


Notes:

- 1、Repetitive Rating:Pulse Width Limited by Maximum Junction Temperature.
- 2、L = 10.0mH, I<sub>AS</sub> =14.0A, V<sub>DD</sub> = 100V, R<sub>G</sub> = 25 Ω, Starting T<sub>J</sub> = 25°C.
- 3、I<sub>SD</sub>≤20.0A, di/dt≤200A/μs, V<sub>DD</sub>≤BV<sub>DSS</sub>, Starting T<sub>J</sub> = 25°C.
- 4、Pulse Test : Pulse Width ≤300 μ s, Duty Cycle≤2%.
- 5、Essentially Independent of Operating Temperature.


**SMT20N65**

650V N-Channel MOSFET


### On-Region Characteristics




### Transfer Characteristics




### On-Resistance Variation vs. Drain Current and Gate Voltage




### Body Diode Forward Voltage Variation vs. Source Current and Temperature



### Capacitance Characteristics







### Gate Charge Characteristics



**SMT20N65**

650V N-Channel MOSFET

**Breakdown Voltage Variation  
vs. Temperature****On-Resistance Variation  
vs. Temperature****Maximum Safe Operating Area****Maximum Drain Current  
Vs. Case Temperature**


**SMT20N65**

650V N-Channel MOSFET

**TO-220C Package Dimensions**

UNIT: mm

SYMBOL	min	nom	max	SYMBOL	min	nom	max
A	4.00	4.40	4.80	E	9.40	9.90	10.40
B	1.17	1.32	1.47	e		2.54	
B1	0.91	1.06	1.21	F	1.15	1.30	1.45
b1	0.65	0.80	0.95	L	12.00	13.00	14.00
c	0.40	0.50	0.60	L1	2.50	3.00	3.50
D	14.90	15.90	16.90	Q	2.30	2.80	3.30
D1	6.10	6.60	7.10	Q1	1.90	2.40	2.90
W	9.50	10.00	10.50	φP	3.40	3.65	3.90
S		8.30		Z	0		0.20
φH		1.50		N		3 °	
G		0.10		V		3 °	





**SMT20N65**

**650V N-Channel MOSFET**

注意事项：

- 1、在电路设计时请不要超过器件的最大额定值，否则会影响整机的可靠性。
- 2、MOSFET产品为静电敏感型器件，使用时应注意采取防静电保护措施，如佩戴防静电手环、设备接地等。
- 3、如需安装散热片，请注意控制扭力大小及散热片的平整度。
- 4、该规格书由华科公司制作，并可能不定期更改，恕不另行通知。
- 5、如有疑问，请及时联系我司销售代表。

版本履历表：

序号	版本号	修改时间	修改记录
1	V1.0	2022-12-20	首次发行