



HCD70R350-S1


700V N-Channel Super Junction Power MOSFET

● Features:

- 13.0A, 700V, $R_{DS(on)(Typ)} = 310m\Omega @ V_{GS}=10V$
- Low Gate Charge
- Low C_{rss}
- 100% Avalanche Tested
- Fast Switching
- Improved dv/dt Capability

● Application:

- High Frequency Switching Mode Power Supply
- Active Power Factor Correction



Absolute Maximum Ratings ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{DSS}	Drain-Source Voltage	700	V
I_D	Drain Current - Continuous ($T_c=25^\circ\text{C}$) - Continuous ($T_c=100^\circ\text{C}$)	13.0*	A
		8.2*	A
I_{DM}	Drain Current - Pulsed (Note1)	52*	A
V_{GSS}	Gate-Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy (Limit Reference Value) (Note2)	248	mJ
I_{AR}	Avalanche Current (Note1)	5.0	A
E_{AR}	Repetitive Avalanche Energy (Note1)	5.9	mJ
dv/dt	Peak Diode Recovery dv/dt (Note3)	8.5	V/ns
P_D	Power Dissipation ($T_c = 25^\circ\text{C}$) - Derate above 25°C	96	W
		0.77	W/ $^\circ\text{C}$
T_j	Operating Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55 to +150	$^\circ\text{C}$

* Drain Current Limited by Maximum Junction Temperature.

Thermal Characteristics

Symbol	Parameter	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case	1.3	$^\circ\text{C} / \text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	69	$^\circ\text{C} / \text{W}$

	HCD70R350-S1
	700V N-Channel Super Junction Power MOSFET


Electrical Characteristics(Tc=25°C unless otherwise noted)

Symbol	Parameter	Test Conditons	Min	Typ	Max	Unit
Off Characteristics						
BV _{DSS}	Drain-source Breakdown Voltage	V _{GS} =0V ,I _D =250μA	700	--	--	V
ΔBV _{DSS} /ΔT _J	Breakdown Voltage Temperature Coefficient	I _D =250μA (Referenced to 25°C)	--	0.70	--	V/°C
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =700V,V _{GS} =0V	--	--	1	μA
		V _{DS} =560V,Tc=125°C	--	--	10	μA
I _{GSSF}	Gate-Body Leakage Current,Forward	V _{GS} =+30V, V _{DS} =0V	--	--	100	nA
I _{GSSR}	Gate-Body Leakage Current,Reverse	V _{GS} =-30V, V _{DS} =0V	--	--	-100	nA
On Characteristics						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D =250μA	2.0	--	4.5	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} =10 V, I _D =6.5A	--	310	350	mΩ
g _{FS}	Forward Transconductance	V _{DS} =20 V, I _D =6.5A (Note4)	--	6.3	--	S
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =100V,V _{GS} =0V, f=1.0MHz	--	1050	--	pF
C _{oss}	Output Capacitance		--	46	--	pF
C _{rss}	Reverse Transfer Capacitance		--	1.1	--	pF
Switching Characteristics						
t _{d(on)}	Turn-On Delay Time	V _{DD} = 350 V, I _D = 13 A, R _G = 25 Ω (Note4,5)	--	23	--	ns
t _r	Turn-On Rise Time		--	47	--	ns
t _{d(off)}	Turn-Off Delay Time		--	63	--	ns
t _f	Turn-Off Fall Time		--	36	--	ns
Q _g	Total Gate Charge	V _{DS} = 560 V, I _D =13.0 A, V _{GS} = 10 V (Note4,5)	--	27.1	--	nC
Q _{gs}	Gate-Source Charge		--	9.1	--	nC
Q _{gd}	Gate-Drain Charge		--	12.2	--	nC
Drain-Source Diode Characteristics and Maximum Ratings						
I _S	Maximum Continuous Drain-Source Diode Forward Current		--	--	13.0	A
I _{SM}	Maximum Pulsed Drain-Source Diode Forward Current		--	--	52	A
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} =0V,I _S =13.0A	--	--	1.4	V
t _{rr}	Reverse Recovery Time	V _{GS} =0V, I _S =13A, d I _F /dt=100A/μs (Note4)	--	350	--	ns
Q _{rr}	Reverse Recovery Charge		--	4.8	--	μC


Notes:

- 1、Repetitive Rating:Pulse Width Limited by Maximum Junction Temperature.
- 2、 $L=18mH, I_{AS}=5.0A, V_{DD}=100V, R_G=25\Omega$, Starting $T_J=25^\circ C$.
- 3、 $I_{SD}\leq 13.0A, di/dt\leq 200A/\mu s, V_{DD}\leq BV_{DSS}$, Starting $T_J=25^\circ C$.
- 4、Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
- 5、Essentially Independent of Operating Temperature.


On-Regin Characteristics




Transfer Characteristics




On-Resistance Variation vs. Drain Current and Gate Voltage




Body Diode Forward Voltage Variation vs. Source Current and Temperature



Capacitance Characteristics



Gate Charge Characteristics







HCD70R350-S1

700V N-Channel Super Junction Power MOSFET


**Breakdown Voltage Variation
vs. Temperature**




**On-Resistance Variation
vs. Temperature**



Maximum Safe Operating Area




**Maximum Drain Current
Vs. Case Temperature**



TO-252 Package Dimensions

UNIT: mm

SYMBOL	min	nom	max	SYMBOL	min	nom	max
A	6.40		6.60	D	2.90		3.10
A1	5.20		5.40	D1	0.45		0.55
A2	4.40		4.60	D2	0.45		0.55
A3	4.40		4.60	e		2.30	
A4	0		0.15	E	2.20		2.40
A5	4.65		4.95	F	0.45		0.55
B	5.90		6.20	G		1.70	
B1	1.57		1.77	L	1.40		1.60
C	0.90		0.96	θ (度)	0		10.00



	HCD70R350-S1
	700V N-Channel Super Junction Power MOSFET

注意事项:

- 1、在电路设计时请不要超过器件的最大额定值，否则会影响整机的可靠性。
- 2、MOSFET产品为静电敏感型器件，使用时应注意采取防静电保护措施，如佩戴防静电手环、设备接地等。
- 3、如需安装散热片，请注意控制扭力大小及散热片的平整度。
- 4、该规格书由华科公司制作，并可能不定期更改，恕不另行通知。
- 5、如有疑问，请及时联系我司销售代表。

版本履历表:

序号	版本号	修改时间	修改记录
1	V1.0	2022-12-20	首次发行